

# FM-A400-1

## Specifications

Foam Volume Output	38 lpm
Solutions Usage	50 lph
Average Drop Interval	2.4 seconds
Ribbon Foam Capable	Good
In-Cab Density Control	Yes
Overall Dimensions	550mm x 450mm x 270mm
Mounting Footprints	4 Bolts on Back Plate
Air Source	Remote Supply
Maximum Amperage	12 Amps
Shipping Weight	12 Kg

## Parts List

Part Number	Description	Qty Required
TFM1414	¼" Brass Nipple	2
TFT1414FF	¼" Female Brass Tee	1
TFRB1418	¼" to 1/8" Brass Reducing Bush	3
TFRB3414	¾" to ¼" Brass Reducing Bush	1
TFEL1414MM	¼" Male Brass Elbow	1
TFRB3418	¾" to 1/8" Brass Reducing Bush	1
AA144F-1-3	Directional Valve 3 Way Operational	1
LST075-HB	Poly T Strainer Head	1
FL5100-040	Pump Air Driven Santoprene	1
A240023	Nipple ¾" to ½" reducing	1
A-SHM34	Poly ¾" Hose Mender	2
BALL12F2M	½" Ball Valve Female to Male	1
TFEL1414FF	¼" Female Brass Elbow	1
A-EL1238	Poly ½" to 3/8" Elbow	2
A-M1200	Poly ½" Nipple	1
A-TT14	Poly ¼" Tee	1
A-A1438	Poly ¼" to 3/8" Tail	1
TR38HC	3/8" Hose Clamp	5
TR34HC	3/4 " Hose Clamp	4
L-G1400	63mm Gauge 0-400 Kpa	1
FC0814	M/Out Flow Control 8mm to ¼"	1
QF0814M	Quick Fit Male Connector 8mm to ¼"	2
QF1818	Quick Fit Connector 1/8"	4
TFA1438	¼" to 3/8" Brass Tail	1
FM-400	Foam Marker Cover	1
FM-NRV14	¼" Non Return Valve	1
AAB122ML-12P100	½" 100 Mesh Filter	1
FM-402	Foam Marker Backing Plate	1
L-E1022	Solenoid Valve	1
FM-403	Regulator Assembly	1
HCVT20	Hose 20mm Clear	1m
HPW08	Hose 8mm	1m
A-EL1234	Poly ½" to ¾" Elbow	2
A-F3400	Poly ¾ Plug	1

